

## TSBC-HW-SRV-MID Server for TSBC-SW



The TelcoBridges **TSBC-HW-SRV-MID** is a carrier-grade hardware platform to run the TSBC-SW session border controller designed for Network-to-network interface (NNI SBC), peering and access functions (access SBC).

Reaching performances up to 30,000 concurrent sessions with session establishment rates of 500 sessions per seconds under attack, the TSBC-HW-SRV-MID is the most cost-effective session border controller hardware platform for service providers currently available on the market. This specific hardware configuration has been tested and approved by TelcoBridges to guarantee the performances behavior of the product.

### Product Characteristics:

- ✓ 1U slim form factor
- ✓ Integrated hardware RAID1
- ✓ 10GE or GigE configuration
- ✓ Out-of-band management

Please refer to the TSBC-SW datasheet for a detailed description of supported SBC functionalities.

### TSBC-HW-SRV-MID Data Sheet

**TelcoBridges Inc.**  
91 de la Barre, suite 01  
Boucherville, QC  
J4B 2X6, CANADA

**Sales** +1.450.655.8993  
**TB Support** +1.866.438.4703

[info@telcobridges.com](mailto:info@telcobridges.com)  
[sbc.telcobridges.com](http://sbc.telcobridges.com)

## Characteristics

Single Xeon E3-1240, 4C/8T, 3.5GHz  
 16GB RAM RDIMM, 2400MHz  
 2x 200GB SSD  
 NUMA optimized for PCIe faster accesses  
 Dell iDRAC8 out-of-band interface

## Interfaces

### Configuration for 10GE interfaces:

Management: 2x GigE copper  
 Control: 2x GigE copper  
 VoIP: 2x 10GBASE-T

### Configuration for GigE interfaces:

Management: 2x GigE copper  
 Control: 2x GigE copper  
 VoIP: 6x GigE copper

## High Availability & Redundancy

Power supply redundancy  
 Hardware RAID1 on SSD

## Electrical Characteristics

100 to 240 VAC, 50/60 Hz  
 Hot-swap redundant power supplies  
 Maximum 350W power consumption

## Performance

Metrics	Performance
Max. nb. of concurrent sessions (no transcoding)	30,000
Max. nb. of concurrent sessions (with all channels transcoded)	15,000
Max. nb. of completed sessions per seconds (CPS/CSPS)	1,000
Max. nb. of sessions attempts per seconds (CAPS/SAPS)	
when refused by routed destination endpoint	1,400
when refused by routing engine	2,000
when refused while in congestion	5,400
Max. nb. of registration per seconds (RPS)	4,200
Max. nb. of registration refresh per seconds (RRPS)	18,000
Max. nb. registered devices <sup>1</sup>	350,000

(1) With one contact per address-of-record (AOR)

## Dimensions & Weight

1U, 19" rackmount  
 1.68" (42.8 mm) H x 18.99" (482.4 mm) W x  
 24" (610 mm) D  
 30.42 lbs (13.8 kg)

## Environmental

Operating temperature:  
 +5 to +40 °C, 5% to 85% rel. hum. with 29°C maximum  
 dew point, non-condensing.  
 Storage temperature:  
 -40 to +65 °C, 5% to 95% rel. hum. with 33°C maximum  
 dew point, non-condensing.  
 RoHS compliant

## Regulatory Compliance

CISPR 22/CISPR 24  
 CE Mark Class A  
 EN 55022/55024  
 IEC/EN 60950-1